

## Product Dimension Summary Sheet (2010)

Model	Width (O.D.)		Length (O.D.)		Heights to bottom of				Overall Height (O.D.)		Weight	
	in.	cm.	in.	cm.	Inlet (4")		Outlet ( 1 1/2")		in.	cm.	Pound	Kg.
1 - P - 700	48"	120	96"	245	53"	135	27"	70	63"	160	6660	3020
1 - P - 1000	61"	155	98"	250	53"	135	27"	70	65"	165	8620	3909
1 - P - 1200	72"	180	102"	255	62"	155	27"	70	72"	180	12,500	5669
1 - P - 1500	72"	180	120"	300	62"	155	27"	70	72"	180	14,300	6486
2 - P 2000	84"	213	156"	396	56"	142	26"***	66	70"	177		
2400 T- tank	10'	300	N/A		68"	172	27"*	70	81"	250	24,680	11194
4100T - tank	10'	300	N/A		115"	287	27"*	70	128"	325	34,800	15784
GMH pump chamber	36" Base 30" chamber	75	N/A		N/A		N/A		175"	444	2,900	1315
300 (O.T.R.)	32"	80	88"	225	N/A		Holding Tank		31"	80	2,000	907
500	48"	122	64"	162	50"	127	27"	70	65"	165	5,040	2286
1600	102"	260	102"	260	TOP		Holding Tank		55"	138	11,500	5216
Floor Drain Sump	12"	30	16"	40	N/A		6"	15	15"	38	262	119
City Sump	30"	75	30"	75	N/A		4" @13" 6" @ 9"	4" @ 33" 6" @ 22"	24"	60	1116	506
Single Garage Sump (80 gal. )	29"	73	29"	73	N/A		19"	N/A	43"	109	1220	553
Double Garage Sump (140 gal.)	30"	75	56"	140	N/A		28" 45°@18"	71 45	44"	110	2530	1147
Concrete Parking Curbs	8"	20.32	8'	245	N/A		N/A	N/A	7"	17.78	347	157.4
Concrete Parking Curbs	8"	20.32	6'	183	N/A		N/A	N/A	7"	17.78	285	129.3
Concrete Barriers	26.5"	67.31	96"	245	N/A		N/A	N/A	26.5"	67.31	2690	1220
Lego Blocks	30"	76.2	60"	152.4	N/A		N/A	N/A	30"	76.2	4267	1936
Tuf-Stop Parking Curbs	6"	15.24	36" or 72"		N/A		N/A	N/A	5"	12.7	124	56.25

\* 1 1/2" Brass outlet Double Female

\*\* 2" PVC Sch 40 Coupling

### Tank Capacities

Model	Total Tank		Working		Pump		Siphon		Dosing Volume
	Gals.	L	Gals.	L	Gals.	L	Gals.	L	gal./inch
1 -P -700	700	3150	420	1900	165	750	75	340	4.1
1-P-1000	1000	4500	600	2700	250	1135	100	455	5.3
1-P1200	1200	5400	750	3375	300	1350	120	540	5.7
1-P-1500	1500	3750	950	4275	350	1575	135	608	6.3
2000 T- tank	2000	9000	1500	6720	450	2025	180	810	8.6
4100 T - tank	4100	18450	2850	12825	900	4050	N/A	N/A	8.6
2000 5 bdrm	2000	9092	1293	5878	613	2786			
2000 6 bdrm	2000	9092	1430	6500	475	2159			

## Product Dimension Summary Round Tanks

Total Tank Capacity			Diameter		Height of tank excluding manhole		Weight	
Model	Gals	Litres	Ft.	cm.	Ft.	cm.	Pound	K.g.
1500	1500	6800	8'	240	6' - 8"	205	12960	5879
1800	1800	8200	8'	240	7' - 8"	235	14300	6486
2000	2000	9100	8'	240	8' - 8"	265	15490	7026
2300	2300	10450	8'	240	9' - 8"	295	16080	7294
2600	2600	11800	8'	240	10' - 8"	325	17420	7902
2900	2900	13200	8'	240	11' - 8"	355	18610	8441
2000	2000	9100	10'	300	5' - 9"	175	17250	7824
2400	2400	10900	10'	300	6' - 9"	205	19540	8863
3300	3300	15000	10'	300	8' - 8"	265	21820	9897
3700	3700	16800	10'	300	9' - 8"	295	24100	1094
4100	4100	18600	10'	300	10' - 8"	325	25960	11775
5000	5000	22500	11'	330	11' - 2"	335	39200	17709
1750G Ring	1750	7955	10'	300	4'4"	131	7510	3405
2500G Ring	2500	11365	11'	330	5'7"	152	13930	6320

24" ID Concrete Collars (60cm)			
Length		Weight	
Inches	cm	pound	K.g.
12"	30	180	81
18"	45	260	117
24"	60	340	154
36"	90	520	235

30" ID Concrete Collars (75 cm)			
Length		Weight	
Inches	cm	pound	Kg
12"	180	240	108
18"	260	360	163
24"	340	480	217
36"	520	710	322

Tank Lids		
Size	Weight	
	pound	K.g.
24"	100	45
28"	150	68
30"	150	68

**NOTE:**

~ All tanks are imperial gallons

~ All water cisterns have a 24" ID manhole 24" high, cast into the center of the tank.

~ All water cisterns have an 1 1/4" brass female threaded coupling for suction line 22" from the bottom of the tank.

~ All holding tanks have a 24" ID manhole with no extensions off to one side.

~ All holding tanks will have 2 - 4" ABS coup. cast into tank and a 6" ABS coup. cast into manhole lid.